

# Anytone AT-D868UV Settings on PiStar

Stop screen flashing by Blocking Talker Alias -

DMR EmbeddedLCOnly:      TURN ON

DMR DumpTADData:         TURN ON

DMR Configuration	
Setting	Value
DMR Master:	BM_United_States_3103
BrandMeister Network:	Repeater Information   Edit Repeater (BrandMeister Selfcare)
DMR Colour Code:	1
DMR EmbeddedLCOnly:	<input checked="" type="checkbox"/>
DMR DumpTADData:	<input checked="" type="checkbox"/>

Under Expert - MMDVMhost – settings  
[xxx.xxx.xxx.xxx/admin/expert/edit\\_mmdvmhost.php](http://xxx.xxx.xxx.xxx/admin/expert/edit_mmdvmhost.php)

TXInvert = 0

(Set to 0 as your running a Hotspot not a Repeater)

TXOffset = 0

RXOffset = 0

BER rate - Can be 50, 0, -50 for some radios

We find 0 is best

**ALL OTHER SETTINGS DO NOT CHANGE IF DIFFRENT TO PHOTO**  
Will differ with updates and hardware your using

Modem	
Port	/dev/ttyACM0
TXInvert	0
RXInvert	0
PTTInvert	0
TXDelay	100
RXOffset	50
TXOffset	50
DMRDelay	0
RXLevel	50
TXLevel	50
CWIdTXLevel	50
D-StarTXLevel	50
DMRTXLevel	50
YSFTXLevel	50
P25TXLevel	50
RSSIMappingFile	/usr/local/etc/RSSI.dat
Trace	0
Debug	0